EUROPA RANGE

Three possible configurations : single room
partitioned room
placed room

► TECHNICAL DATA

		MA60	MA100	MA150
MANUFACTURE		Injected PU sandwich panels		
FACING	Wall and ceilings	RAL 9002 pebble white powder-coated 5 mm ribbed galvanised steel sheet		
	Floor	**Standard 30** : plasticised film-coated 6 mm grey steel sheet bonded to 10 mm CTBX plywood Uniform load : 3000 kg/m² Concentrated static load : 400 kg/60cm² Dynamic load on trolley with 4 rubber wheels : 500 kg/4 wheels		
		Option reinforced 40 : 6 mm checkerplate stainless bonded to steel sheet reinforced CTBX plywood Uniform load : 4000 kg/m² Concentrated static load : 500 kg/60cm² Dynamic load on trolley with 4 rubber wheels : 800 kg/4 wheels		
INSULATION	Walls and ceilings	60 mm PU	100 mm PU	150 mm PU
	Floor	Total thickness 60 mm	Total thickness 100 mm	Total thickness 150 mm
U VALUE	Walls and ceilings	0,346 W/m²°C	0,212 W/m²°C	0,143 W/m²°C
	Floor	0,346 W/m²°C	0,212 W/m²°C	0,143 W/m²°C
TEMPERATURE	Loss 10W/m²	25°C	45°C	65°C
	Loss 13W/m²	35°C	60°C	85°C
INSIDE DIMENSIONS	Length x width	40 – 80 – 120 – 160 – 200 – 240 – 280 … (in multiples of 40 cm)		
	Height	201,5 – 221,5 – 241,5 …(in multiples of 40 cm)		
OUTSIDE DIMENSIONS	Length x width	Multiples of 40 + 12 cm	Multiples of 40 + 20 cm	Multiples of 40 + 30 cm
	Height with floor	Multiples of 40 cm + 13,5 cm + ceiling suspension	Multiples of 40 cm + 27,5 cm + ceiling suspension (with bearers)	Multiples of 40 cm + 37,5 cm + ceiling suspension (with bearers)

For all other dimensions : please contact us